

LITHIUM BATTERY

Primary lithium batteries ER14250M

**3.6V Primary lithium-thionyl chloride
(Li-SOCl₂) Power type
1/2AA -size spiral cell**


For high drain/high pulses applications requesting superior voltage response in -55°C~+85°C environments.

Cell size references (1/2 AA)

Electrical characteristics (typical values relative to cells stored for one year or less at +30°C max.)	
Nominal capacity (at 0.5 mA +20°C 2.0V cut off. The capacity resbred by the cell varies according to current drain, temperature and cut off).	0.75Ah
Open circuit voltage (at +20°C)	3.66V
Nominal voltage (at 0.5mA +20°C)	3.6V
Pulse capability: Typically up to 400 mA (400 mA/0.1 second pules, drained every 2 mn at +20°C from undischarged cells with 10 μ A base current, yield voltage readings above 3.0V. The readings may vary accöding to the pulse characteristics, the temperature, and the cell' s previous history. Fitting the cell with a capacitor may be recommended in severe conditions. Consult pbq)	
Max. Continuous current	200mA
Max. Pulse current	400mA
Storage (recommended) (for more severe conditions, consult pbq)	+30°C max
Operating temperature range (Operation above ambient T may lead to reduced capacity and lower voltage readings at the begining of pulses. Consult pbq)	-55°C / +85°C
Physical characteristics	
Diammeter (max)	14.5mm(0.57 in)
Height (max)	25mm(1 in)
Typical weight	10g(0.327oz)
Available termination suffix	radial tabs, radial pins, axia leads, flying leads

LITHIUM BATTERY

ER14250M



Key features

- ▶ High and stable operating voltage
- ▶ Superior drain capability
- ▶ Low self-discharge rate (less than 1% after 1 year of storage at +20°C)
- ▶ Hermetic glass-to-metal sealing
- ▶ Notch technology for safety vent
- ▶ Non-flammable electrolyte
- ▶ Finished product with PTC to avoid short-circuit

Main applications

- ▶ Radiocommunication and other military applications
- ▶ Alarms and security systems
- ▶ Beacons and emergency location transmitters
- ▶ GPS
- ▶ Metering systems
- ▶ Sonobuoys
- ▶ LED lighting applications
- ▶ Others

Storage


- ▶ The storage area should be clean, cool (not exceeding +30°C), dry and ventilated.

Warning


- ▶ Do not use if the battery casing was mangled.
- ▶ Don't use different models of battery in series.
- ▶ Do not try to recharge.

Characteristic curves

Discharge performance (25°C)



Capacity VS Current



Voltage VS Temperature

