

General purpose batteries

12 volt range

With a range of well over 50 models, pbq offers one of the widest selections in the battery industry. The batteries are designed with the cost and quality conscious user in mind offering an excellent price/performance ratio. The functional life is 4-5 years at an operating temperature of 25°C.

Typical applications:

- toys
- household appliances
- sensors
- UPS systems
- integrated emergency power supplies
- telecommunication equipment
- garden tools

VdS approved VRLA Batteries

The VdS-approved pbq batteries form a special range that has been tested and qualified by the German VdS institute. The concept behind VdS recognition; ensuring tested and certified quality in the products and services being offered in the safety and security markets, is of equally advantageous for user and supplier.

Flame Retardant ABS Casing

All VdS models are accomplished in Flame Retardant ABS casing. Due to the right choice of the flame retardant, the batteries remain RoHS Compliant.

VdS Models

Model pbq...	Capacity in Ah	VdS Number
pbq 1,2-12	1,2	G104102
pbq 2,3-12	2,3	G104103
pbq 3,2-12	3,2	G104104
pbq 7-12	7	G104049
pbq 12-12	12	G104087
pbq 18-12F	18	G108009
pbq 26-12F	26	G108010
pbq 40-12F	40	G108011
pbq 65-12F	65	G108087

Models available

Model pbq...	Capacity in Ah	Dimensions (LxWxH1/H2)	Weight
pbq 0,8-12F	0,8	96x25x62mm	340gr
pbq 1,2-12	1,2	97x48x52/58mm	630gr
pbq 1,3-12	1,3	97x48x52/58mm	630gr
pbq 2,3-12	2,3	178x35x61/67mm	990gr
pbq 2,6-12	2,6	178x34x61/67mm	990gr
pbq 2,9-12	2,9	79x55,5x98,5/104mm	1,18kg
pbq 3,2-12	3,2	134x67x61/67mm	1,4kg
pbq 3,4-12	3,4	134x67x61/67mm	1,4kg
pbq 4-12F	4	195x47x70/76mm	1,58kg
pbq 5,2-12U	5,2	90x70x102/106mm	1,7kg
pbq 7-12	7	151x65x93,5/100mm	2,32kg
pbq 12-12	12	151x98x95/101mm	3,67kg
pbq 18-12F	18	181x77x167mm	5,4kg
pbq 26-12F	26	165x176x127mm	8,4kg
pbq 28-12W	28	165x125x175mm	9,9kg
pbq 40-12F	40	197x165x170mm	13,3kg
pbq 65-12F	65	350x167x179/186mm	21,2kg

Typical applications:


- VdS & NCP approved alarm systems
- Fire & burglar alarmsystems

Quality Control

All pbq batteries are being produced against ISO 9001 and UL quality control standards. Furthermore, batteries are inspected again using a method of statistical analyses upon arrival in the central warehouses. At pbq we understand that a defective battery can mean loss of information, productivity, customers and increased service cost, all 'features' you can do without!



12 volt General Purpose family



Voltage : 12 Volt
Capacity : 26Ah
Appr. dimensions : 166x175x127mm (LxWxH)
Terminal : M5 Nut & Bolt (*supplied*)
Container & lid : Flame Retardant ABS
Approximate weight : 8.4kg
Certificate(s) : CE, UL, VdS
RoHS Compliant : Yes

Typical Applications:

- UPS Systems
- Fire & burglar alarm systems
- Household appliances
- Garden tools
- Telephone exchanges
- Sensors
- Measurement devices




Capacity
 20 hour rate (1.3A) : 26Ah
 10 hour rate (2.47A) : 24.7Ah
 5 hour rate (4.42A) : 22.1Ah
 1 hour rate (15.7A) : 15.7Ah
 15 min. rate (44.6A) : 11.15Ah

Internal Resistance (fully charged) : 12mOhm

Capacity versus temperature
 40°C : 102%
 25°C : 100%
 0°C : 85%
 -15°C : 65%

Max. discharge current : 390A (5 sec)

Charge (constant voltage)
 Maximum charge current 7.8A
 Float use: 13.6 - 13.8 Volt. -20mV/°C
 Cyclic use: 14.5 - 14.9 Volt. -30mV/°C



Discharge data watt/battery

	Discharge time	5 min	10 min	15 min	30 min	1 hr	3 hr	5 hr	10 hr	20 hr
End Voltage	10,80V	946	654	483	280	174	44,9	51,1	28,4	15,0
	10,20V	1006	687	508	312	182	80,8	52,8	29,1	15,6
	9,60V	1060	733	530	323	188	82,3	53,8	29,6	15,6